



Ihr Ansprechpartner /  
Your Partner:

dataTec AG  
E-Mail: info@datatec.eu  
>>> [www.datatec.eu](http://www.datatec.eu)

Mess- und Prüftechnik. Die Experten.

# EVO HIGH VOLTAGE POWER SUPPLY

## Output Voltage up to 20 kV DC



### High Voltage Power Supplies of the EVO Series are the New Generation of DC Power Supplies

Simple handling is combined with speed and high precision

The high voltage power supplies of the EVO series offer fast control at high precision. They are particularly comfortable to operate. Their compact build needs only 2U, which is extraordinary for their power density of 2 kW and 3 kW.


The units are characterized by high performance as well as fast and precise control. The high voltage output can be reversed remotely and supplies either a positive or negative high voltage at the output.

A microcontroller, combined with an FPGA (Field Programmable Gate Array) permits particularly precise control. This makes complete and digital control of the EVO power supplies possible.

Our customers use the EVO e.g. for HV tests in the production and verification of semiconductors, for end-of-line tests and in the research and development environment.

FPGAs are used in high voltage power supplies since they permit quick signal processing and flexible adaptation to various load requirements.

### Typical Applications



Semiconductor tests /  
manufacturing



Solarmodule  
tests



HV  
tests



E-mobility  
tests



Coating  
processes

### EVO-Series Highlights

- Voltage classes:  
0 ... 1.5 kV DC  
0 ... 5 kV DC  
0 ... 10 kV DC  
0 ... 20 kV DC
- Power: 500 W, 2 kW or 3 kW
- Current: up to 2 A
- Fully digital regulation
- Usable as 19" rack-mount or benchtop, with integrated adapter
- Compact (12.5 kg), 2U
- Wide range AC input, singlephase
- Ethernet and RS232 on board
- Output polarity remote reversible

# EVO HIGH VOLTAGE POWER SUPPLY

## Technical Data

### General

|                 |  |
|-----------------|--|
| Function        | Digitally regulated DC high voltage power supply   |
| Input voltage   | 230 V $\pm 10\%$ (3 kW version)<br>187 V – 253 V (2 kW version)<br>Active power factor correction<br>Mains socket on rear side<br>(IEC 60320 Type C20) |
| Input frequency | 47 ... 63 Hz   |
| Input current   | type-dependent (max. 16 A)   |
| Operating temp. | 0 °C ... 40 °C   |

### Displays

- Colored 3.5" TFT screen with LED backlight
- Just 3 buttons for full manual control
- Menu navigation by clear structure and sub menus
- Configurable code protection for sub menus
- Error and event monitoring including time tags (actual and shadow)

### Output

|                                  |  |
|----------------------------------|--|
| Discharge time<br>(without load) | <60 s (type-dependent)   |
| Output voltage                   | reversible polarity, positive or negative (connected to earth) |
| Output socket                    | Female Heinzinger HV connector on rear side                    |

### Digital Interface for remote control

- Ethernet and RS232
- SCPI command set
- LabView driver on request

### Enclosure

|        |   |
|--------|---|
| Design | Benchtop, 19"-Rack-Mount<br>Steel chassis |
| Height | 2U (89 mm)                                |
| Depth  | 500 mm                                    |
| Weight | approx. 12.5 kg                           |

### Voltage stabilization

|  |                                    |
|--|------------------------------------|
| Setting range (approx.)  | 0.01 % to 100 % $U_{nom}$          |
| Setting accuracy<br>(manual operation)                                 | 16 bit                             |
| Line regulation<br>(at $\pm 10\%$ mains voltage change)                | < $\pm 0.01\%$ $U_{nom}$           |
| Load regulation<br>(on load step from 10 % to 90 %)                    | $\leq 0.05\%$ $U_{nom}$            |
| Response time<br>(on load current change<br>from deviation 0 to 100 %) | <1 ms to 0.1 % $U_{nom}$           |
| Stability<br>(under constant conditions)                               | $\leq 0.01\%$ $U_{nom}$ over 8 h   |
| Temperature coefficient  | $\leq 0.01\%$ $U_{nom} / K$        |
| Ripple   | $\leq 0.01\%$ $U_{nom} \pm 100$ mV |

### Current stabilization

|  |                                    |
|--|------------------------------------|
| Setting range (approx.)  | 0.01 % to 100 % $I_{nom}$          |
| Setting accuracy<br>(manual operation)                                 | 16 bit                             |
| Line regulation<br>(at $\pm 10\%$ mains voltage change)                | < $\pm 0.01\%$ $I_{nom}$           |
| Load regulation<br>(on load step from 0 to 100 %)                      | $\leq 0.05\%$ $I_{nom}$            |
| Response time<br>(on load current change<br>from deviation 0 to 100 %) | <1 ms to 0.1 % $I_{nom}$           |
| Stability<br>(under constant conditions)                               | $\leq 0.01\%$ $I_{nom}$ over 8 h   |
| Temperature coefficient  | $\leq 0.01\%$ $I_{nom} / K$        |
| Ripple   | $\leq 0.01\%$ $I_{nom} \pm 100$ mA |

### Scope of supply

- Heinzinger EVO HV unit according to type description
- Male Heinzinger HV plug with 3 m HV Cable
- Rubber feet for benchtop application
- Power cable 1.5 m, with CEE7 connector on grid and terminal block for I/O plug

## Accessories / Options:

### EVO ramp control

This option facilitates controlled upward and downward regulation with an adjustable gradient. The adjustable range lies between 1 V/s and 10  $U_{nom}$  V/s. This option can be retrofitted.

### EVO ARC detection

This option facilitates the detection of flashovers in the output voltage, which the device can report, and also switches off the output voltage if desired.

# Product Summary EVO

| Type                | Power (W) | Voltage (V) | Current (mA) | Height (U) | Rack Depth (mm) | Weight (kg) | Part number   |
|---------------------|-----------|-------------|--------------|------------|-----------------|-------------|---------------|
| EVO 1500 - 1400 flo | 2,000     | 1,500       | 1,400        | 2          | 500             | 12.5        | 00.210.113.4  |
| EVO 1500 - 1400     |           | 1,500       | 1,400        |            |                 |             | 00.210.113.x* |
| EVO 5000 - 400      |           | 5,000       | 400          |            |                 |             | 00.210.143.x* |
| EVO 10000 - 200     |           | 10,000      | 200          |            |                 |             | 00.210.163.x* |
| EVO 1500 - 2000     | 3,000     | 1,500       | 2,000        |            |                 |             | 00.210.114.x* |
| EVO 5000 - 600      |           | 5,000       | 600          |            |                 |             | 00.210.144.x* |
| EVO 10000 - 300     |           | 10,000      | 300          |            |                 |             | 00.210.164.x* |
| EVO 20000 - 25      |           | 500         | 20,000       |            |                 |             | 25            |

\*These devices are available with positive (...1) or negative (...9) polarity, as well as electrically reversible (...5) polarity.

## Technical Drawing



Mess- und Prüftechnik. Die Experten.

**Ihr Ansprechpartner /  
Your Partner:**

**dataTec AG**

E-Mail: [info@datatec.eu](mailto:info@datatec.eu)

>>> [www.datatec.eu](http://www.datatec.eu)

**Heinzinger electronic GmbH**

Anton-Jakob-Str. 4  
83026 Rosenheim  
Germany

+49 (0) 8031 2458 0  
[info@heinzinger.de](mailto:info@heinzinger.de)  
[www.heinzinger.com](http://www.heinzinger.com)